



FRONT FACE DETAIL
(COVER REMOVED)

Ø2.00" LEAD HOLE Ø2.50" KNOCKOUT
 3/8-16 UNC-2B THRU - 1 HOLE
 Ø.53-.58 8 HOLES (284 FR. MAY HAVE ONLY 4 HOLES)
 1/2-13 UNC-2B .75 FULL THD. 4 HOLES

- NOTES:
1. CONDUIT BOX BE ROTATED IN 90° STEPS.
 2. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.
 3. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.

DASH	FRAME	B	C	2F	2XF	BS	AC
1275	284TC	12.50	27.08	9.50		4.75	20.39
1425	284/6TC	13.00	28.58	11.00	9.50	5.50	21.89

UNLESS SPECIFIED		TOLERANCES IN INCHES		DRAWN MSG 04-30-2001	
DEC.	INCHES	ML	X	CHK	ML
		TAT	07-06-2004	ML	X
4	REDRAWN IN AUTOCAD	CN	29100-2392	ML	XX
3	4.503/4.500 NOW 4.500/4.970	CAV	12-28-2001	ML	XX
2	ADDED NOTE 3	CAV	12-11-2001	BW	XXX
1	NEW DRAWING	MSG	05-03-2001	TB	XXXX
NO.	REVISION	BY & DATE	CHK	ANG	±7.30"
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT.					
DRAWN MSG 04-30-2001		SCALE 1=6		REV. OF	
CHK	ML 05-03-2001	TITLE OUTLINE - STEEL C' BOX - TFNA		PAGE	
APPD	TB 05-03-2001	280TC FR.-C' FACE-TENV-STD 12.50 LAM		OF	
REF		MATL		SS311154	
		FINISH		4	
		PREV		B	
		CAD FILE SS311154		SIZE DRAWING NO.	
				B	
				DIST LB	