

ALUMINUM WOUND, THREE PHASE



Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

208 Primary Volts 480 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007BK	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011BK	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014BK	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020BK	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027BK	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034BK	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040BK	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051BK	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063BK	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075BK	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093BK	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118BK	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145BK	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175BK	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220BK	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275BK	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330BK	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440BK	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550BK	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660BK	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075CCS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

230 Primary Volts 230 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007CC	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011CC	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014CC	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020CC	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027CC	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034CC	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040CC	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051CC	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063CC	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075CC	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093CC	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118CC	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145CC	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175CC	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220CC	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275CC	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330CC	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440CC	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550CC	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660CC	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075CCS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

ALUMINUM WOUND, THREE PHASE



Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

460 Primary Volts		230 Secondary Volts				60 Hz		
kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007JC	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011JC	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014JC	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020JC	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027JC	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034JC	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040JC	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051JC	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063JC	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075JC	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093JC	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118JC	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145JC	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175JC	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220JC	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275JC	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330JC	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440JC	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550JC	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660JC	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075JCS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

460 Primary Volts		400 Secondary Volts				60 Hz		
kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007JH	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011JH	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014JH	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020JH	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027JH	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034JH	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040JH	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051JH	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063JH	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075JH	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093JH	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118JH	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145JH	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175JH	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220JH	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275JH	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330JH	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440JH	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550JH	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660JH	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075JHS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

ALUMINUM WOUND, THREE PHASE



Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

460 Primary Volts

460 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type		Wiring Diagram (Pages 272-281)
			Width	Depth	Height		W - Wall	F - Floor	
7.5	DM007JJ	NH5	19.40	20.20	21.50	150	F or W *	SCD 8	
11	DM011JJ	NH5	19.40	20.20	21.50	160	F or W *	SCD 8	
14	DM014JJ	NH5	19.40	20.20	21.50	170	F or W *	SCD 8	
20	DM020JJ	NH6	23.90	25.00	28.75	240	F or W *	SCD 7	
27	DM027JJ	NH6	23.90	25.00	28.75	300	F or W *	SCD 7	
34	DM034JJ	NH6	23.90	25.00	28.75	330	F or W *	SCD 7	
40	DM040JJ	NH6	23.90	25.00	28.75	350	F or W *	SCD 7	
51	DM051JJ	NH6	23.90	25.00	28.75	430	F or W *	SCD 7	
63	DM063JJ	NH3	26.00	25.00	38.00	530	F	SCD 7	
75	DM075JJ	NH3	26.00	25.00	38.00	580	F	SCD 7	
93	DM093JJ	NH3	26.00	25.00	38.00	630	F	SCD 7	
118	DM118JJ	NH3	26.00	25.00	38.00	730	F	SCD 7	
145	DM145JJ	NH4	32.00	29.50	41.00	830	F	SCD 7	
175	DM175JJ	NH4	32.00	29.50	41.00	930	F	SCD 7	
220	DM220JJ	NJ1	39.50	34.00	51.50	1350	F	SCD 9	
275	DM275JJ	NJ1	39.50	34.00	51.50	1500	F	SCD 9	
330	DM330JJ	NJ1	39.50	34.00	51.50	1700	F	SCD 9	
440	DM440JJ	NJ2	48.50	38.40	59.00	2100	F	SCD 10	
550	DM550JJ	NJ2	48.50	38.40	59.00	2350	F	SCD 10	
660	DM660JJ	NJ3	51.50	43.40	66.00	2900	F	SCD 10	

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075JJS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

480 Primary Volts

240 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type		Wiring Diagram (Pages 272-281)
			Width	Depth	Height		W - Wall	F - Floor	
7.5	DM007KD	NH5	19.40	20.20	21.50	150	F or W *	SCD 8	
11	DM011KD	NH5	19.40	20.20	21.50	160	F or W *	SCD 8	
14	DM014KD	NH5	19.40	20.20	21.50	170	F or W *	SCD 8	
20	DM020KD	NH6	23.90	25.00	28.75	240	F or W *	SCD 7	
27	DM027KD	NH6	23.90	25.00	28.75	300	F or W *	SCD 7	
34	DM034KD	NH6	23.90	25.00	28.75	330	F or W *	SCD 7	
40	DM040KD	NH6	23.90	25.00	28.75	350	F or W *	SCD 7	
51	DM051KD	NH6	23.90	25.00	28.75	430	F or W *	SCD 7	
63	DM063KD	NH3	26.00	25.00	38.00	530	F	SCD 7	
75	DM075KD	NH3	26.00	25.00	38.00	580	F	SCD 7	
93	DM093KD	NH3	26.00	25.00	38.00	630	F	SCD 7	
118	DM118KD	NH3	26.00	25.00	38.00	730	F	SCD 7	
145	DM145KD	NH4	32.00	29.50	41.00	830	F	SCD 7	
175	DM175KD	NH4	32.00	29.50	41.00	930	F	SCD 7	
220	DM220KD	NJ1	39.50	34.00	51.50	1350	F	SCD 9	
275	DM275KD	NJ1	39.50	34.00	51.50	1500	F	SCD 9	
330	DM330KD	NJ1	39.50	34.00	51.50	1700	F	SCD 9	
440	DM440KD	NJ2	48.50	38.40	59.00	2100	F	SCD 10	
550	DM550KD	NJ2	48.50	38.40	59.00	2350	F	SCD 10	
660	DM660KD	NJ3	51.50	43.40	66.00	2900	F	SCD 10	

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075KDS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

ALUMINUM WOUND, THREE PHASE



Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

480 Primary Volts		480 Secondary Volts				60 Hz		
kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007KK	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011KK	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014KK	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020KK	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027KK	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034KK	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040KK	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051 KK	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063KK	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075KK	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093KK	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118KK	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145KK	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175KK	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220KK	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275KK	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330KK	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440KK	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550KK	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660KK	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075KKS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

575 Primary Volts		460 Secondary Volts				60 Hz		
kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007NJ	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011NJ	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014NJ	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020NJ	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027NJ	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034NJ	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040NJ	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051 NJ	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063NJ	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075NJ	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093NJ	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118NJ	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145NJ	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175NJ	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220NJ	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275NJ	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330NJ	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440NJ	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550NJ	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660NJ	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075NJS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

ALUMINUM WOUND, THREE PHASE



Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

575 Primary Volts 575 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007NN	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011NN	NH5	19.40	20.20	21.50	160	F or W *	SCD 8
14	DM014NN	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
20	DM020NN	NH6	23.90	25.00	28.75	240	F or W *	SCD 7
27	DM027NN	NH6	23.90	25.00	28.75	300	F or W *	SCD 7
34	DM034NN	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
40	DM040NN	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
51	DM051NN	NH6	23.90	25.00	28.75	430	F or W *	SCD 7
63	DM063NN	NH3	26.00	25.00	38.00	530	F	SCD 7
75	DM075NN	NH3	26.00	25.00	38.00	580	F	SCD 7
93	DM093NN	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118NN	NH3	26.00	25.00	38.00	730	F	SCD 7
145	DM145NN	NH4	32.00	29.50	41.00	830	F	SCD 7
175	DM175NN	NH4	32.00	29.50	41.00	930	F	SCD 7
220	DM220NN	NJ1	39.50	34.00	51.50	1350	F	SCD 9
275	DM275NN	NJ1	39.50	34.00	51.50	1500	F	SCD 9
330	DM330NN	NJ1	39.50	34.00	51.50	1700	F	SCD 9
440	DM440NN	NJ2	48.50	38.40	59.00	2100	F	SCD 10
550	DM550NN	NJ2	48.50	38.40	59.00	2350	F	SCD 10
660	DM660NN	NJ3	51.50	43.40	66.00	2900	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers. (i.e. DM075NNS)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.

COPPER WOUND, THREE PHASE

Selection Tables

Listed are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

208 Primary Volts 480 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
7.5	DM007BKCN	NH5	19.40	20.20	21.50	150	F or W *	SCD 8
11	DM011BKCN	NH5	19.40	20.20	21.50	170	F or W *	SCD 8
14	DM014BKCN	NH5	19.40	20.20	21.50	210	F or W *	SCD 8
20	DM020BKC	NH6	23.90	25.00	28.75	270	F or W *	SCD 7
27	DM027BKC	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
34	DM034BKC	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
40	DM040BKC	NH6	23.90	25.00	28.75	380	F or W *	SCD 7
51	DM051BKC	NH6	23.90	25.00	28.75	450	F or W *	SCD 7
63	DM063BKC	NH3	26.00	25.00	38.00	550	F	SCD 7
75	DM075BKC	NH3	26.00	25.00	38.00	600	F	SCD 7
93	DM093BKC	NH3	26.00	25.00	38.00	630	F	SCD 7
118	DM118BKC	NH3	26.00	25.00	38.00	880	F	SCD 7
145	DM145BKC	NH4	32.00	29.50	41.00	930	F	SCD 7
175	DM175BKC	NH4	32.00	29.50	41.00	1100	F	SCD 7
220	DM220BKC	NH4	32.00	29.50	41.00	1450	F	SCD 9
275	DM275BKC	NJ1	39.50	34.00	51.50	1680	F	SCD 9
330	DM330BKC	NJ1	39.50	34.00	51.50	1850	F	SCD 9
440	DM440BKC	NJ2	48.50	38.40	59.00	2350	F	SCD 10
550	DM550BKC	NJ2	48.50	38.40	59.00	2800	F	SCD 10
660	DM660BKC	NJ3	51.50	43.40	66.00	3250	F	SCD 10

For shielded units, please replace the suffix "C" with a 'K' on the above part numbers. (i.e. DM075BKK)

* OPTIONAL WALL MOUNTING KIT AND/OR DRIP PLATE KIT REQUIRED.