

ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE



208 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009BB	NH5	19.40	20.20	21.50	140	F or W *	SCD 25
15	MK015BB	NH5	19.40	20.20	21.50	180	F or W *	SCD 25
30	MK030BB	NH6	23.90	25.00	28.75	300	F or W *	SCD 9
45	MK045BB	NH6	23.90	25.00	28.75	400	F or W *	SCD 9
75	MK075BB	NH3	26.00	25.00	38.00	575	F	SCD 9
12.5	MK112BB	NH3	26.00	25.00	38.00	750	F	SCD 9
150	MK150BB	NH4	32.00	29.50	41.00	900	F	SCD 9
225	MK225BB	NH4	32.00	29.50	41.00	1350	F	SCD 9
300	MK300BB	NJ1	39.50	34.00	51.50	1550	F	SCD 9
500	MK500BB	NJ2	48.50	38.40	59.00	2400	F	SCD 25
750	MK750BB	NJ3	51.50	43.40	66.00	3450	F	SCD 25

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED.

208 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009BK	NH5	19.40	20.20	21.50	140	F or W *	SCD 23
15	MK015BK	NH5	19.40	20.20	21.50	180	F or W *	SCD 23
30	MK030BK	NH6	23.90	25.00	28.75	300	F or W *	SCD 26
45	MK045BK	NH6	23.90	25.00	28.75	400	F or W *	SCD 26
75	MK075BK	NH3	26.00	25.00	38.00	575	F	SCD 26
12.5	MK112BK	NH3	26.00	25.00	38.00	750	F	SCD 26
150	MK150BK	NH4	32.00	29.50	41.00	900	F	SCD 26
225	MK225BK	NH4	32.00	29.50	41.00	1350	F	SCD 26
300	MK300BK	NJ1	39.50	34.00	51.50	1550	F	SCD 26
500	MK500BK	NJ2	48.50	38.40	59.00	2400	F	SCD 23
750	MK750BK	NJ3	51.50	43.40	66.00	3450	F	SCD 23

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED.

240 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009DB	NH5	19.40	20.20	21.50	140	F or W *	SCD 25
15	MK015DB	NH5	19.40	20.20	21.50	180	F or W *	SCD 25
30	MK030DB	NH6	23.90	25.00	28.75	300	F or W *	SCD 9
45	MK045DB	NH6	23.90	25.00	28.75	400	F or W *	SCD 9
75	MK075DB	NH3	26.00	25.00	38.00	575	F	SCD 9
12.5	MK112DB	NH3	26.00	25.00	38.00	750	F	SCD 9
150	MK150DB	NH4	32.00	29.50	41.00	900	F	SCD 9
225	MK225DB	NH4	32.00	29.50	41.00	1350	F	SCD 9
300	MK300DB	NJ1	39.50	34.00	51.50	1550	F	SCD 9
500	MK500DB	NJ2	48.50	38.40	59.00	2400	F	NO TAPS
750	MK750DB	NJ3	51.50	43.40	66.00	3450	F	NO TAPS

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED.

ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE



240 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009DK	NH5	19.40	20.20	21.50	140	F or W *	SCD 23
15	MK015DK	NH5	19.40	20.20	21.50	180	F or W *	SCD 23
30	MK030DK	NH6	23.90	25.00	28.75	300	F or W *	SCD 26
45	MK045DK	NH6	23.90	25.00	28.75	400	F or W *	SCD 26
75	MK075DK	NH3	26.00	25.00	38.00	575	F	SCD 26
12.5	MK112DK	NH3	26.00	25.00	38.00	750	F	SCD 26
150	MK150DK	NH4	32.00	29.50	41.00	900	F	SCD 26
225	MK225DK	NH4	32.00	29.50	41.00	1350	F	SCD 26
300	MK300DK	NJ1	39.50	34.00	51.50	1550	F	SCD 26
500	MK500DK	NJ2	48.50	38.40	59.00	2400	F	NO TAPS
750	MK750DK	NJ3	51.50	43.40	66.00	3450	F	NO TAPS

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

480 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009KB	NH5	19.40	20.20	21.50	140	F or W *	SCD 25
15	MK015KB	NH5	19.40	20.20	21.50	180	F or W *	SCD 25
30	MK030KB	NH6	23.90	25.00	28.75	300	F or W *	SCD 19
45	MK045KB	NH6	23.90	25.00	28.75	400	F or W *	SCD 19
75	MK075KB	NH3	26.00	25.00	38.00	575	F	SCD 19
12.5	MK112KB	NH3	26.00	25.00	38.00	750	F	SCD 19
150	MK150KB	NH4	32.00	29.50	41.00	900	F	SCD 19
225	MK225KB	NH4	32.00	29.50	41.00	1350	F	SCD 19
300	MK300KB	NJ1	39.50	34.00	51.50	1550	F	SCD 19
500	MK500KB	NJ2	48.50	38.40	59.00	2400	F	SCD 19
750	MK750KB	NJ3	51.50	43.40	66.00	3450	F	SCD 19

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

480 Delta Primary Volts

240 Delta/120 CT Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009KD	NH5	19.40	20.20	21.50	140	F or W *	SCD 13
15	MK015KD	NH5	19.40	20.20	21.50	180	F or W *	SCD 13
30	MK030KD	NH6	23.90	25.00	28.75	300	F or W *	SCD 21
45	MK045KD	NH6	23.90	25.00	28.75	400	F or W *	SCD 21
75	MK075KD	NH3	26.00	25.00	38.00	575	F	SCD 21
12.5	MK112KD	NH3	26.00	25.00	38.00	750	F	SCD 21
150	MK150KD	NH4	32.00	29.50	41.00	900	F	SCD 21
225	MK225KD	NH4	32.00	29.50	41.00	1350	F	SCD 21
300	MK300KD	NJ1	39.50	34.00	51.50	1550	F	SCD 21
500	MK500KD	NJ2	48.50	38.40	59.00	2400	F	SCD 22
750	MK750KD	NJ3	51.50	43.40	66.00	3450	F	SCD 22

For shielded units, please add the suffix "S" to the above part numbers.
The 120V lighting tap is limited to 5% of nameplate kVA rating divided by 3.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE



480 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009KK	NH5	19.40	20.20	21.50	140	F or W *	SCD 25
15	MK015KK	NH5	19.40	20.20	21.50	180	F or W *	SCD 25
30	MK030KK	NH6	23.90	25.00	28.75	300	F or W *	SCD 19
45	MK045KK	NH6	23.90	25.00	28.75	400	F or W *	SCD 19
75	MK075KK	NH3	26.00	25.00	38.00	575	F	SCD 19
12.5	MK112KK	NH3	26.00	25.00	38.00	750	F	SCD 19
150	MK150KK	NH4	32.00	29.50	41.00	900	F	SCD 19
225	MK225KK	NH4	32.00	29.50	41.00	1350	F	SCD 19
300	MK300KK	NJ1	39.50	34.00	51.50	1550	F	SCD 19
500	MK500KK	NJ2	48.50	38.40	59.00	2400	F	SCD 20
750	MK750KK	NJ3	51.50	43.40	66.00	3450	F	SCD 20

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

600 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009PB	NH5	19.40	20.20	21.50	140	F or W *	SCD 10
15	MK015PB	NH5	19.40	20.20	21.50	180	F or W *	SCD 10
30	MK030PB	NH6	23.90	25.00	28.75	300	F or W *	SCD 9
45	MK045PB	NH6	23.90	25.00	28.75	400	F or W *	SCD 9
75	MK075PB	NH3	26.00	25.00	38.00	575	F	SCD 9
12.5	MK112PB	NH3	26.00	25.00	38.00	750	F	SCD 9
150	MK150PB	NH4	32.00	29.50	41.00	900	F	SCD 9
225	MK225PB	NH4	32.00	29.50	41.00	1350	F	SCD 9
300	MK300PB	NJ1	39.50	34.00	51.50	1550	F	SCD 9
500	MK500PB	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MK750PB	NJ3	51.50	43.40	66.00	3450	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE



600Y Primary Volts

240 Delta Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009PD	NH5	19.40	20.20	21.50	140	F or W *	SCD 29
15	MK015PD	NH5	19.40	20.20	21.50	180	F or W *	SCD 29
30	MK030PD	NH6	23.90	25.00	28.75	300	F or W *	SCD 16
45	MK045PD	NH6	23.90	25.00	28.75	400	F or W *	SCD 16
75	MK075PD	NH3	26.00	25.00	38.00	575	F	SCD 16
12.5	MK112PD	NH3	26.00	25.00	38.00	750	F	SCD 16
150	MK150PD	NH4	32.00	29.50	41.00	900	F	SCD 16
225	MK225PD	NH4	32.00	29.50	41.00	1350	F	SCD 16
300	MK300PD	NJ1	39.50	34.00	51.50	1550	F	SCD 16
500	MK500PD	NJ2	48.50	38.40	59.00	2400	F	SCD 29
750	MK750PD	NJ3	51.50	43.40	66.00	3450	F	SCD 29

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

600 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
9	MK009PK	NH5	19.40	20.20	21.50	140	F or W *	SCD 10
15	MK015PK	NH5	19.40	20.20	21.50	180	F or W *	SCD 10
30	MK030PK	NH6	23.90	25.00	28.75	300	F or W *	SCD 9
45	MK045PK	NH6	23.90	25.00	28.75	400	F or W *	SCD 9
75	MK075PK	NH3	26.00	25.00	38.00	575	F	SCD 9
12.5	MK112PK	NH3	26.00	25.00	38.00	750	F	SCD 9
150	MK150PK	NH4	32.00	29.50	41.00	900	F	SCD 9
225	MK225PK	NH4	32.00	29.50	41.00	1350	F	SCD 9
300	MK300PK	NJ1	39.50	34.00	51.50	1550	F	SCD 9
500	MK500PK	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MK750PK	NJ3	51.50	43.40	66.00	3450	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.