

Dimensions NEMA T Range - Foot Mounted

FRAME A ALUMINUM	*AA	AB	AF	B	BA	C	D	2E	2F	G	H	J	P	T	O	V	ES	N-W	R	S	U	
143T	7.0	2X.75	5.5	2.3	5.4	2.25	14.8	3.50	5.5	4.00	0.16	0.34	1.4	7.1	-	7.0	2.00	1.41	2.250	0.771	0.188	0.875
145T	7.0	2X.75	5.5	2.3	6.0	2.25	14.8	3.50	5.5	5.00	0.16	0.34	1.4	7.1	-	7.0	2.00	1.41	2.250	0.771	0.188	0.875
182T	9.0	2X1	6.5	2.3	6.9	2.75	17.7	4.50	7.5	4.50	0.16	0.41	1.6	8.8	1.90	8.9	2.50	1.78	2.750	0.986	0.250	1.125
184T	9.0	2X1	6.5	2.3	6.9	2.75	17.7	4.50	7.5	5.50	0.16	0.41	1.6	8.8	1.90	8.9	2.50	1.78	2.750	0.986	0.250	1.125
213T	10.4	2X1	7.3	2.3	8.8	3.50	20.5	5.25	8.5	5.50	0.20	0.41	1.6	10.4	1.40	10.4	3.12	2.41	3.380	1.201	0.312	1.375
215T	10.4	2X1	7.3	2.3	8.8	3.50	20.5	5.25	8.5	7.50	0.20	0.41	1.6	10.4	1.40	10.4	3.12	2.41	3.380	1.201	0.312	1.375
FRAME A CAST IRON																						
*AA AB AF B BA C D 2E 2F G H J P T O V ES N-W R S U																						
143T	6.9	2X.75	5.5	2.0	6.6	2.25	14.8	3.50	5.5	4.00	0.60	0.34	1.6	7.4	-	7.2	2.15	1.41	2.250	0.771	0.188	0.875
145T	6.9	2X.75	5.5	2.0	6.6	2.25	14.8	3.50	5.5	5.00	0.60	0.34	1.6	7.4	-	7.2	2.15	1.41	2.250	0.771	0.188	0.875
182T	9.1	2X1	6.5	2.3	7.8	2.75	17.7	4.50	7.5	4.50	0.65	0.41	1.8	9.3	1.50	9.3	2.65	1.78	2.750	0.986	0.250	1.125
184T	9.1	2X1	6.5	2.3	7.8	2.75	17.7	4.50	7.5	5.50	0.65	0.41	1.8	9.3	1.50	9.3	2.65	1.78	2.750	0.986	0.250	1.125
213T	10.3	2X1	7.3	2.3	9.6	3.50	20.5	5.25	8.5	5.50	0.70	0.41	2.0	11.2	1.80	10.9	3.28	2.41	3.380	1.201	0.312	1.375
215T	10.3	2X1	7.3	2.3	9.6	3.50	20.5	5.25	8.5	7.50	0.70	0.41	2.0	11.2	1.80	10.9	3.28	2.41	3.380	1.201	0.312	1.375
254T	12.6	2X1.25	10.0	3.5	13.3	4.25	28.6	6.25	10.0	8.25	0.70	0.53	2.8	13.0	1.60	12.5	3.90	2.91	4.000	1.416	0.375	1.625
256T	12.6	2X1.25	10.0	3.5	13.3	4.25	28.6	6.25	10.0	10.00	0.70	0.53	2.8	13.0	1.60	12.5	3.90	2.91	4.000	1.416	0.375	1.625
284TS	14.0	2X1.5	11.0	3.5	13.8	4.75	28.0	7.00	11.0	9.50	0.87	0.53	3.0	14.7	0.70	14.5	3.10	1.91	3.250	1.416	0.375	1.625
284T	14.0	2X1.5	11.0	3.5	13.8	4.75	28.0	7.00	11.0	11.00	0.87	0.53	3.0	14.7	0.70	14.5	3.10	1.91	3.250	1.416	0.375	1.625
286TS	14.0	2X1.5	11.0	3.5	13.8	4.75	28.0	7.00	11.0	9.50	0.87	0.53	3.0	14.7	0.70	14.5	3.10	1.91	3.250	1.416	0.375	1.625
286T	14.0	2X1.5	11.0	3.5	13.8	4.75	28.0	7.00	11.0	11.00	0.87	0.53	3.0	14.7	0.70	14.5	3.10	1.91	3.250	1.416	0.375	1.625
324TS	16.0	2X2	13.0	4.4	15.0	5.25	30.0	8.00	12.5	10.50	1.10	0.66	3.3	17.0	1.70	15.9	3.50	2.03	3.750	1.591	0.500	1.875
324T	15.5	2X2	13.0	4.4	15.0	5.25	31.5	8.00	12.5	12.00	1.10	0.66	3.4	17.0	1.40	16.2	5.10	3.91	5.250	1.845	0.500	2.125
326TS	19.0	2X2	13.0	4.4	15.0	5.25	30.0	8.00	12.5	10.50	1.20	0.66	3.3	17.0	1.70	15.9	3.50	2.03	3.750	1.591	0.500	1.875
326T	15.5	2X2	13.0	4.4	15.0	5.25	31.5	8.00	12.5	12.00	1.20	0.66	3.4	17.0	1.40	16.2	5.10	3.91	5.250	1.845	0.500	2.125
364TS	17.4	2X2	13.8	4.4	17.2	5.88	32.0	9.00	14.0	11.25	1.10	0.66	3.5	18.5	1.30	18.2	3.60	2.03	3.750	1.591	0.500	1.875
364T	17.4	2X2	13.8	4.4	17.2	5.88	34.1	9.00	14.0	12.25	1.10	0.66	3.5	18.5	1.30	18.2	5.73	4.28	5.880	2.021	0.625	2.375
365TS	17.4	2X2	13.8	4.4	17.2	5.88	32.0	9.00	14.0	11.25	1.10	0.66	3.5	18.5	1.30	18.2	3.60	2.03	3.750	1.591	0.500	1.875
365T	17.4	2X2	13.8	4.4	17.2	5.88	34.1	9.00	14.0	12.25	1.10	0.66	3.5	18.5	1.30	18.2	5.73	4.28	5.880	2.021	0.625	2.375
404T	19.5	2X3	15.6	7.6	19.9	6.62	40.3	10.00	16.0	12.25	1.42	0.81	4.1	22.8	0.90	19.7	7.10	5.65	7.250	2.450	0.750	2.875
405TS	19.5	2X3	15.6	7.6	19.9	6.62	37.3	10.00	16.0	13.75	1.42	0.81	4.1	22.8	0.90	19.7	4.10	2.78	4.250	1.845	0.500	2.125
405T	19.5	2X3	15.6	7.6	19.9	6.62	40.3	10.00	16.0	13.75	1.42	0.81	4.1	22.8	0.90	19.7	7.10	5.65	7.250	2.450	0.750	2.875
444TS	21.7	2X3	18.5	7.6	22.0	7.50	43.7	11.00	18.0	14.50	1.36	0.81	4.6	24.5	2.25	20.4	4.50	3.03	4.750	2.021	0.625	2.375
444T	21.7	2X3	18.5	7.6	22.0	7.50	43.7	11.00	18.0	16.50	1.36	0.81	4.6	24.5	2.25	20.4	4.20	3.03	4.750	2.021	0.625	2.375
445TS	21.7	2X3	18.5	7.6	22.0	7.50	43.7	11.00	18.0	16.50	1.36	0.81	4.6	24.5	2.25	20.4	4.20	3.03	4.750	2.021	0.625	2.375
445T	21.7	2X3	18.5	7.6	22.0	7.50	47.5	11.00	18.0	16.50	1.36	0.81	4.6	24.5	2.25	20.4	4.25	6.91	8.500	2.880	0.875	3.375
447TS	21.7	2X3	18.5	7.6	29.0	7.50	49.6	11.00	18.0	20.00	1.36	0.81	4.6	24.5	2.25	20.4	4.50	3.03	4.750	2.021	0.625	2.375
447T	21.7	2X3	18.5	7.6	29.0	7.50	56.0	11.00	18.0	20.00	1.36	0.81	4.6	24.5	2.25	20.4	4.62	8.50	10.125	2.880	0.875	3.375
449TS	25.6	2X3	21.3	3.2	46.8	7.50	69.5	11.00	18.0	25.00	1.33	0.81	6.0	26.7	4.60	24.4	4.50	3.03	4.750	2.021	0.625	2.375
449T	25.6	2X3	21.3	3.2	46.8	7.50	75.0	11.00	18.0	25.00	1.33	0.81	6.0	26.7	4.60	24.4	9.62	8.50	10.125	2.880	0.875	3.375

*AA - NPSC Threads as Standard