

# Dimensions NEMA T Range - C Face - D Flange

FRAME	*AA	AB	AF	C	ES	N-W	P	T	V	R	S	U	
143T	2X.75	5.5	2.0	14.8	1.41	2.250	7.4		2.15	0.771	0.188	0.875	
145T	2X.75	5.5	2.0	14.8	1.41	2.250	7.4		2.15	0.771	0.188	0.875	
182T	2X1	6.5	2.3	17.7	1.78	2.750	9.3	1.50	2.65	0.986	0.250	1.125	
184T	2X1	6.5	2.3	17.7	1.78	2.750	9.3	1.50	2.65	0.986	0.250	1.125	
213T	2X1	7.3	2.3	20.5	2.41	3.380	11.2	1.80	3.28	1.201	0.312	1.375	
215T	2X1	7.3	2.3	20.5	2.41	3.380	11.2	1.80	3.28	1.201	0.312	1.375	
254T	2X1.25	10.0	3.5	26.6	2.91	4.000	13.0	1.60	3.90	1.416	0.375	1.625	
256T	2X1.25	10.0	3.5	26.6	2.91	4.000	13.0	1.60	3.90	1.416	0.375	1.625	
284TS	2X1.5	11.0	3.5	28.0	1.91	3.250	14.7	0.70	3.10	1.416	0.375	1.625	
284T	2X1.5	11.0	3.5	29.5	3.28	4.620	14.7	0.70	4.47	1.591	0.500	1.875	
286TS	2X1.5	11.0	3.5	28.0	1.91	3.250	14.7	0.70	3.10	1.416	0.375	1.625	
286T	2X1.5	11.0	3.5	29.5	3.28	4.620	14.7	0.70	4.47	1.591	0.500	1.875	
324TS	2X2	13.0	4.4	30.0	2.03	3.750	17.0	1.70	3.50	1.591	0.500	1.875	
324T	2X2	13.0	4.4	31.5	3.91	5.250	17.0	1.40	5.10	1.845	0.500	2.125	
326TS	2X2	13.0	4.4	30.0	2.03	3.750	17.0	1.70	3.50	1.591	0.500	1.875	
326T	2X2	13.0	4.4	31.5	3.91	5.250	17.0	1.40	5.10	1.845	0.500	2.125	
364TS	2X2	13.8	4.4	32.0	2.03	3.750	18.5	1.30	3.60	1.591	0.500	1.875	
364T	2X2	13.8	4.4	34.1	4.28	5.880	18.5	1.30	5.73	2.021	0.625	2.375	
365TS	2X2	13.8	4.4	32.0	2.03	3.750	18.5	1.30	3.60	1.591	0.500	1.875	
365T	2X2	13.8	4.4	34.1	4.28	5.880	18.5	1.30	5.73	2.021	0.625	2.375	
404T	2X3	15.6	7.6	40.3	5.65	7.250	22.8	0.90	7.10	2.450	0.750	2.875	
405TS	2X3	15.6	7.6	37.3	2.78	4.250	22.8	0.90	4.10	1.845	0.500	2.125	
405T	2X3	15.6	7.6	40.3	5.65	7.250	22.8	0.90	7.10	2.450	0.750	2.875	
444TS	2X3	18.5	7.6	43.7	3.03	4.750	24.5	2.25	4.50	2.021	0.625	2.375	
444T	2X3	18.5	7.6	47.5	6.91	8.500	24.5	2.25	8.25	2.880	0.875	3.375	
445TS	2X3	18.5	7.6	43.7	3.03	4.750	24.5	2.25	4.50	2.021	0.625	2.375	
445T	2X3	18.5	7.6	47.5	6.91	8.500	24.5	2.25	8.25	2.880	0.875	3.375	
447TS	2X3	18.5	7.6	49.6	3.03	4.750	24.5	2.25	4.50	2.021	0.625	2.375	
447T	2X3	18.5	7.6	55.0	8.50	8.500	24.5	2.25	9.62	2.880	0.875	3.375	
C FLANGE													
FRAME	AJ	AK	BB	BC	BD	BF	D FLANGE						
FRAME	AJ	AK	BB	BC	BD	BF	AJ	AK	BB	BC	BD	BE	BF
143T	5.875	4.5	0.16	0.12	6.50	4X3/8-16	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
145T	5.875	4.5	0.16	0.12	6.50	4X3/8-16	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
182T	7.250	8.5	0.25	0.12	9.00	4X1/2-13	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
184T	7.250	8.5	0.25	0.12	9.00	4X1/2-13	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
213T	7.250	8.5	0.25	0.25	9.00	4X1/2-13	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
215T	7.250	8.5	0.25	0.25	9.00	4X1/2-13	10.00	9.0	0.25	0.00	11.00	0.50	4X0.53
254T	7.250	8.5	0.25	0.25	10.00	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
256T	7.250	8.5	0.25	0.25	10.00	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
284TS	9.000	10.5	0.25	0.25	11.25	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
284T	9.000	10.5	0.25	0.25	11.25	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
286TS	9.000	10.5	0.25	0.25	11.25	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
286T	9.000	10.5	0.25	0.25	11.25	4X1/2-13	12.50	11.0	0.25	0.00	14.00	0.75	4X0.81
324TS	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
324T	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
326TS	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
326T	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
364TS	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
364T	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
365TS	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
365T	11.000	12.5	0.25	0.25	14.00	4X5/8-11	16.00	14.0	0.25	0.00	18.00	0.75	4X0.81
404T	11.000	12.5	0.25	0.25	15.50	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
405TS	11.000	12.5	0.25	0.25	15.50	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
405T	11.000	12.5	0.25	0.25	15.50	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
444TS	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
444T	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
445TS	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
445T	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
447TS	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81
447T	14.000	16.0	0.25	0.25	18.00	4X5/8-11	20.00	18.0	0.25	0.00	22.00	1.00	8X0.81

\*AA - NPSC Threads as Standard